

[CORSAIR]

MIDI DIFFUSED LED BATTEN




Description

The [CORSAIR] Midi Diffused LED Batten delivers high-performance illumination in a robust, lightweight metal housing. Featuring easy installation, it comes standard as tri-colour and wattage selectable. Emergency versions are also available, for versatile application.

Innovative Design

Integrated diffuser and gear tray allow for fast re-assembly.



Key Features

- Wattage and colour selectable for versatility
- Conduit entry points at both ends
- High efficacy up to 125lm/W
- Emergency options available
- PA16 terminal block



**EMERGENCY
FUNCTION**

The [CORSAIR]^E automatically switches to its AS2293-tested emergency function when the mains power supply fails. Featuring over 150 minutes of emergency operation supported by high capacity and long lifetime batteries.

Features:

- 150mins Emergency operation
- Test button for self-test function
- High capacity
- 3 year battery warranty


EMERGENCY SPECIFICATION

Emergency LED Power	2W
Output Current	80V/25mA
Battery Charging Ambient Temp.	0°C ~ +55°C
Battery Model	Cyantronic

Technical Specifications

Rated Life	≥50,000 hours	CRI	>80
Body	Steel, Polycarbonate	Operating Temperature	-20°C to +45°C
Installation	Surface Mount <i>Emergency Models can also be Suspended</i>	Input Voltage	220-240V~ 50/60Hz
Beam Angle	120°	IP Rating	IP20
Power Factor	>0.9	Connection	Terminal Block

Dimensional Drawing



Model	Length mm	Width mm	Height mm	Weight kg
BCM-2-16S120	600	76	66	0.7
BCM-2-16S120-E	600	76	66	0.92
BCM-4-30S120	1200	76	66	1.2
BCM-4-30S120-E	1200	76	66	1.42

Product Data

Part Number	Power	Lumen Output	CCT
BCM-2-16S120*	8W/16W	1000lm-1920lm	Colour Selectable (3000K/4000K/5700K)
BCM-2-16S120-E*	8W/16W	1000lm-1920lm	Colour Selectable (3000K/4000K/5700K)
BCM-4-30S120*	15W/30W	2000lm-3600lm	Colour Selectable (3000K/4000K/5700K)
BCM-4-30S120-E*	15W/30W	2000lm-3600lm	Colour Selectable (3000K/4000K/5700K)

*Sensor Dimmable option available, add 'SD' to model code, eg: BCM-4-30S120-SD / BCM-4-30S120-ESD
Minimum order quantities may apply